


PINNACLE 350 CCT

24V LED Specification Grade CCT Tape Light

TL350-24V-CCT

SPECIFICATION SHEET



DESCRIPTION

NDR Pinnacle 350 CCT Tunable Series LED tape light offers industry specification grade technology and full-range CCT Tunability (2700K-6500K) at an affordable price. With an industry leading 97+ color rendering index, and a high output lumen package of greater than 300LM/ft, this Tape Light is sure to fit your installation needs.

Suitable applications: Kitchen cabinets, shelves, toe kicks, cove lighting, closet spaces & more.

FEATURES

- 3oz. copper
- Thicker layer offers less electrical resistance and voltage drops.
- Cutttable every 4"
- Full range dimmability
- IP20 – Dry locations
- 2700K – 6500K Tunable CCT Range
- Suitable for use in closet spaces

SPECIFICATIONS

| Model | TL350-24V-CCT |
|-----------------------|--|
| Certificates | cULus |
| Input voltage | 24V |
| Watts/FT | 2.9W/FT |
| Lumens/FT | 322 lm/FT |
| Watts/m | 9.5W/m |
| Lumens/m | 1056 lm/m |
| Color temperature | 2700K to 6500K tunable |
| CRI | 97+ |
| Dimmable | Yes |
| IP rating | IP20 |
| Dimensions | 0.4" x 197" x 0.07" (10mm x 5000mm x 1.8mm) |
| Cutttable section | Every 4" (100mm) |
| Beam angle | 120° |
| Lifetime | 50,000 hours |
| Mounting | 3M self-adhesive tape (non-porous) |
| Operating temperature | -4°F to 113°F (-20°C to 45°C) |
| Max run | 26.2ft (8m) |
| Limited warranty | 5 years |

STOCKING SKUs

| Model | Watts/FT | lm/FT | Watts/m | lm/m | CRI | Reel size | IP Rating | Lifetime | Ltd. Warr. |
|------------------------|----------|-------|---------|------|-----|-------------|-----------|----------|------------|
| TL350-24V-CCT | 2.9 | 322 | 9.5 | 1056 | 97+ | 16.4FT (5m) | IP20 | 50,000h | 5 years |
| TL350-24V-CCT30 | 2.9 | 322 | 9.5 | 1056 | 97+ | 98.4FT (5m) | IP20 | 50,000h | 5 years |

RATINGS & CERTIFICATIONS



0-100%
Dimmable



Dry
locations



JAB-2022

ACCESSORIES



TL-DUAL-CCT-3-10

3-Pin screw connector, tape-to-tape & tape-to-wire lead terminal, dual connector (10mm)



TL-SLTT-CCT-3-10

3-Pin screw connector, tape-to-tape 90° L connector (10mm)



TL-STW8-CCT-3-10

3-Pin screw connector, tape to 8" wire lead (10mm)

DRIVERS & CONTROLLERS

Option 1 - All-in-One Dimmer + Driver



TLDCCT24V-96W
TLDCCT24V-96WB
 96W CCT Tunable (2700K-6500K)
 Dimmer and 24V Driver
 120V input, 24V output
 Dry Locations Rated
 Dimensions: 2.1" x 4.1" x 1.4"
 (54mm x 105mm x 35mm)

Option 2 - WIFI Controller + Driver

* Color & brightness tuning via SmartLife app



TL-WIFI-CTLR
 WIFI & RF controller for RGBW
 and RGB-CCT tape light



any of the drivers below



TLD24V-MINI-60W
 60W Class 2 LED transformer
 120V input, 24V output,
 ELV dimming ONLY
 Requires junction box for
 UL rated
 Dimensions: 3.3" x 1.6" x 1"
 (84mm x 40mm x 25mm)



TLD24V-MINI-96W
 96W Class 2 LED transformer
 120V input, 24V output,
 ELV dimming ONLY
 Requires junction box for
 UL rated
 Dimensions: 3.3" x 1.6" x 1"
 (84mm x 40mm x 25mm)




TLD24V-30W
 30W Class 2 LED driver
 100-277V input, 24V output
 TRIAC, ELV, MLV, Forward &
 reverse phase, PWM output
 1/2" knockout size
 Wet locations rated
 Dimensions: 6.5" x 3.7" x 1.6"
 (165mm x 94.5mm x 40mm)



TLD24V-60W
 60W Class 2 LED driver
 100-277V input, 24V output
 TRIAC, ELV, MLV, Forward &
 reverse phase, PWM output
 1/2" knockout size
 Wet locations rated
 Dimensions: 7.4" x 3.7" x 1.6"
 (188mm x 94.5mm x 40mm)

DRIVERS & CONTROLLERS



TLD24V-96W

96W Class 2 LED driver
100-277V input, 24V output
TRIAC, ELV, MLV, Forward &
reverse phase, PWM output
1/2" knockout size
Wet locations rated
Dimensions: 8.7" x 3.7" x 1.6"
(220mm x 94.5mm x 40mm)



TLD24V-192W

192W Class 2 LED driver
100-277V input, 24V output x2
(2x 96W output)
TRIAC, ELV, MLV, Forward &
reverse phase, PWM output
1/2" knockout size
Wet locations rated
Dimensions: 10.9" x 4.3" x 1.8"
(278mm x 110mm x 40mm)



TLD24V-288W

288W Class 2 LED driver
100-277V input, 24V output x3
(3x 96W output)
TRIAC, ELV, MLV, Forward &
reverse phase, PWM output
1/2" knockout size
Wet locations rated
Dimensions: 11.9" x 4.3" x 1.8"
(301mm x 110mm x 45mm)



TLD24V-25W

25W LED driver for Pinnacle Series
Puck Light and Tape Light
120V input, 24V output
Dry location rated
Dimensions: 6.1" x 2.1" x 0.8"
(155mm x 54mm x 20mm)



JBX-TLD-MINI

Aluminum junction box and wiring
compartment enclosure with built-in
separation for 120V and 24V wiring
compartments. Fits both 60W & 96W
"MINI" transformer drivers (sold
separately).
Dimensions 5.0" x 3.1" x 1.6"
(127mm x 79mm x 40mm)