

NEW PRODUCT ANNOUNCEMENT

www.ndrelectric.com

t. 1.514.695.8228 | 1.855.739.8228 f. 1.514.695.9009 | 1.855.812.9009

250 SERIES LED SPECIFICATION GRADE 24V TAPE LIGHT

NDR Pinnacle **250 Series** LED Tape Light offers industry specification grade technology and is engineered for the extra-long run applications. This product features temperature sensing and constant current IC chips that ensure an even consistent light output in long run applications.

As an added plus, installation costs are reduced by requiring fewer drivers and separate runs. Ideal applications: ambient and close level task lighting. Well suited for longer applications such as hallways, toe kicks, coves, display cases and more.

3M[™] ADHESIVE BACK

Easy installation on non-porous surfaces

FIELD CUTTABLE

Can be cut every 2"

CONSTANT CURRENT IC

Ensures every LED receives the same specific amperage level, providing consistent light output and color.

FEATURES


- Constant current IC chips
 - For reduced drop in voltage & light output
 - 4oz Copper per sq. ft. Specification Grade
 - Thicker layer offers less electrical resistance and voltage drops
- 3-Step MacAdam LED binning
- Full range dimmability
- Cuttable every 2"
- 3M[™] mounting tape
- Maximum run 32.8ft (10m)
- IP20 rated Dry location

24CC 100 24CV 95 12CV 90 85 80 75 70 0 Distance (M) 2 4 6 8 1

DOUBLE LAYER COPPER FOIL

4oz pure copper for superior thermal management and lower voltage drop

LUX Drop (%)







MODEL	WATTS / FT	LM / FT	WATTS / M	LM / M	CRI	REEL SIZE	ip Rating	LIFETIME	LIMITED WARRANTY
TL250-CC24V-3K	2.9	236	9.6	768	90+	32.8FT (10M)	חכםו	50,000 HOURS	
TL250-CC24V-4K	2.9	230	9.0	100	90+	32.0F1 (101VI)	IFZU	30,000 NUUNS	J TEANJ